

**Description**

Fastener Length: 3-7/16", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6704D48
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-579-3898
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6704D48 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Nominal
<b>Fastener Length:</b>	3.410 Inches Minimum And 3.440 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.429 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.249 Inches Minimum And 0.250 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	2.990 Inches Minimum And 3.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, Tension, Hex Head, Close Tolerance, A286 Cres, Long Thread, Reduced Major Thread Dia., Nonlocking, 160 Ksi Ftu
<b>Special Features:</b>	Has Drilled Shank, 0.046 In. Dia. Centered 0.178 In. From Screw End
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Uns66286 law Ams5731, Ams5732, Ams5737, Or Ams5853 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Ams2700, Method 1, Type 2 Or Type 8, Class 1 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704D48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.