

P/N NAS6704D49

Description

Fastener Length: 3-31/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS6704D49
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-579-5634
Schedule B:	7318.15.8085
ECCN:	9A991



^{*} See page 2 for technical characteristics

P/N NAS6704D49 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	3.49 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
End Item Identification:	Nimrod 2000 Air Reconnaisance
Nominal Thread Diameter:	0.2500 Inches
Grip Length:	3.06 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.310 Inches Nominal First Hole
Color:	Green Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6704D49 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.