

Description

Fastener Length: 1-3/16", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6704DHU12
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-576-9142
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6704DHU12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	1.160 Inches Minimum And 1.190 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Nominal Mils And 0.439 Nominal Centimeters
Grip Diameter:	0.249 Nominal Mils And 0.250 Nominal Centimeters
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.740 Nominal Mils And 0.760 Nominal Centimeters
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt Tension Hex Head Close Tolerance A286 Cres Long Thread Reduced Major Thread Dia Self Locking And Non Locking 160 Ksi FtU
Special Features:	Item Is Unplated Bolt With A Drilled Shank And Head
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704DHU12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.