

P/N NAS6704DU8

Description

Fastener Length: 15/16", Thread: 1/4-28, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6704DU8

Minimum Qty (MOQ): 5

NSN: 5306-01-308-2889

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6704DU8 Specifications

Thread Class: Thread Direction: Thread Length: Fastener Length: Head Style:	3a Right-hand 0.400 Inches Minimum And 0.450 Inches Maximum 0.910 Inches Minimum And 0.940 Inches Maximum Dished Hexagon
Thread Length: Fastener Length:	0.400 Inches Minimum And 0.450 Inches Maximum 0.910 Inches Minimum And 0.940 Inches Maximum
Fastener Length:	0.910 Inches Minimum And 0.940 Inches Maximum
-	
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.722 Inches Minimum First Hole And 0.772 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6704 Professional/industrial Association Standard
Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator:	Overall Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall Unjf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6704DU8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.