

# P/N NAS6704H2

Military-Fasteners.com

#### Description

Fastener Length: 9/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 7/16",

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS6704H2                                 |
|-------------------------|---|
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-01-205-5913                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6704H2 Specifications

| Thread Class:                                  | За   |
|--|--|
|  |  |
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.400 Inches Minimum And 0.450 Inches Maximum  |
| Fastener Length:                               | 0.535 Inches Minimum And 0.565 Inches Maximum  |
| Head Style:                                    | Dished Hexagon   |
| Head Height:                                   | 0.125 Inches Minimum And 0.140 Inches Maximum  |
| Width Between Flats:                           | 0.429 Inches Minimum And 0.439 Inches Maximum  |
| Hole Diameter:                                 | 0.046 Inches Minimum And 0.056 Inches Maximum  |
| Grip Diameter:                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum  |
| Nominal Thread Diameter:                       | 0.250 Inches   |
| Grip Length:                                   | 0.115 Inches Minimum And 0.135 Inches Maximum  |
| Hole Quantity:                                 | 3  |
| Hole Type:                                     | Drilled  |
| Thread Quantity Per Inch:                      | 28   |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch  |
| Hole Configuration Style:                      | Hexagon Corners  |
| Surface Finish:                                | 32.0 Microinches Bearing Surface Of Head   |
| Surface Finish:                                | 32.0 Microinches Grip  |
| Surface Finish:                                | 32.0 Microinches Threads   |
| Material:                                      | Iron Alloy 660 Overall   |
| Material Document And Classification:          | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall                                     |
| Thread Series Designator:                      | Unjf   |
| Specification/standard Data:                   | 80205-nas6704 Professional/industrial Association Standard   |

### How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6704H2</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.