

P/N NAS6704H2

Description

Fastener Length: 9/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 7/16",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6704H2

Minimum Qty (MOQ): 5

NSN: 5306-01-205-5913

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6704H2 Specifications

3a
Right-hand
0.400 Inches Minimum And 0.450 Inches Maximum
0.535 Inches Minimum And 0.565 Inches Maximum
Dished Hexagon
0.125 Inches Minimum And 0.140 Inches Maximum
0.429 Inches Minimum And 0.439 Inches Maximum
0.046 Inches Minimum And 0.056 Inches Maximum
0.2485 Inches Minimum And 0.2495 Inches Maximum
0.250 Inches
0.115 Inches Minimum And 0.135 Inches Maximum
3
Drilled
28
160000 Pounds Per Square Inch
Hexagon Corners
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Iron Alloy 660 Overall
Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6704 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6704H2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.