

Description

Fastener Length: 1-1/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6704HU10 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5306-01-601-1245 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS6704HU10 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Nominal |
| Fastener Length: | 1.050 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Nominal |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.625 Inches Nominal |
| Hole Quantity: | 3 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Corners |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5853 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704HU10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.