

P/N NAS6704HU11

Description

Fastener Length: 1-1/8", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 7/16

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS6704HU11

Minimum Qty (MOQ): 5

NSN: 5306-01-153-0226

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6704HU11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	1.098 Inches Minimum And 1.128 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6704 Professional/industrial Association Standard

How to Order

