

Description

right hand

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS6704U29 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-581-6661 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6704U29 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Nominal |
| Fastener Length: | 2.222 Inches Minimum And 2.252 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Shoulder Diameter: | 0.264 Inches Minimum First Shoulder And 0.265 Inches Maximum First Shoulder |
| Shoulder Length: | 1.802 Inches Minimum First Shoulder And 1.822 Inches Maximum First Shoulder |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Shoulder Shape: | Round First Shoulder |
| Part Name Assigned By Controlling Agency: | Bolt Tension Hex Head Close Tolerance A286 Cres Long Thread Reduced Major Thread Dia Self Locking And Non Locking 160 Ksi Ftu |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS6704U29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.