

**Description**

Fastener Length: 2-1/4", Thread: 1/4-28, Thread Length: 7/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6704U29X
Minimum Qty (MOQ):	5
NSN:	5306-01-045-2414
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6704U29X Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.400 Inches Minimum And 0.450 Inches Maximum
<b>Fastener Length:</b>	2.222 Inches Minimum And 2.252 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.429 Inches Minimum And 0.439 Inches Maximum
<b>Shoulder Diameter:</b>	0.264 Inches Minimum First Shoulder And 0.265 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	1.802 Inches Minimum First Shoulder And 1.822 Inches Maximum First Shoulder
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6704 Professional/industrial Association Standard

## How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704U29X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.