

Description

Fastener Length: 2-1/4", Thread: 1/4-28, Thread Length: 7/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6704U29X
Minimum Qty (MOQ):	5
NSN:	5306-01-045-2414
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6704U29X Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	2.222 Inches Minimum And 2.252 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Shoulder Diameter:	0.264 Inches Minimum First Shoulder And 0.265 Inches Maximum First Shoulder
Shoulder Length:	1.802 Inches Minimum First Shoulder And 1.822 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6704 Professional/Industrial Association Standard

How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704U29X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.