

Description

NAS6705-20 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS670520
Minimum Qty (MOQ):	2
NSN:	5306-01-465-7417
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



NO IMAGE
AVAILABLE

P/N NAS6705-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	1.704 Inches Minimum And 1.734 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
End Item Identification:	C-17
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt,hex Head,close Tolerance,a286 Cres,long Threads,self-locking And Nonlocking
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall And Ams5732 Assn Std 2nd Material Response Overall And Ams5737 Assn Std 3rd Material Response Overall Or Ams5853 Assn Std 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type II,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6705-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.