

Description

Fastener Length: 39/64", Hole Diameter: 5/64", Thread: 5/16-24, Thread Length: 15/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6705HU2
Minimum Qty (MOQ):	2
NSN:	5306-01-478-1634
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6705HU2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	0.579 Inches Minimum And 0.609 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Grip Diameter:	0.312 Inches Nominal
End Item Identification:	F18 E/f
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Bolt,hexhead,close Tolerance,a286 Cres,longthreads,self Locking And Nonlocking
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6705 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6705HU2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.