

Description

Fastener Length: 1-13/16", Thread: 7/16-20, Thread Length: 0-63/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6706D18
Minimum Qty (MOQ):	1
NSN:	5306-01-517-8379
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6706D18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Minimum And 1.804 Inches Maximum
Fastener Length:	1.819 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Shank Unthreaded Hole Diameter:	0.111 Inches Nominal First Hole
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.747 Inches Nominal First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Special Features:	W/drilled Shank Bolt
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6706D18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.