

**Description**

Fastener Length: 1-13/16", Thread: 7/16-20, Thread Length: 0-63/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6706D18
Minimum Qty (MOQ):	1
NSN:	5306-01-517-8379
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6706D18 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.694 Inches Minimum And 1.804 Inches Maximum
<b>Fastener Length:</b>	1.819 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.219 Inches Minimum And 0.234 Inches Maximum
<b>Width Between Flats:</b>	0.678 Inches Minimum And 0.690 Inches Maximum
<b>Grip Diameter:</b>	0.4360 Inches Minimum And 0.4370 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.111 Inches Nominal First Hole
<b>Nominal Thread Diameter:</b>	0.438 Inches
<b>Grip Length:</b>	1.115 Inches Minimum And 1.135 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.747 Inches Nominal First Hole
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Special Features:</b>	W/drilled Shank Bolt
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6706D18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.