



Military-Fasteners.com

**P/N NAS6706D22**

## Description

Length: 1-61/64", Thread: 3/8-24, Thread Length: 9/16", PTFE, polytetrafluoro, NAS6706 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6706D22                                |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5306-01-571-6248                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS6706D22 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                             | 3a  |
| <b>Thread Direction:</b>                         | Right-hand  |
| <b>Thread Length:</b>                            | 0.578 Inches Nominal  |
| <b>Fastener Length:</b>                          | 1.938 Inches Minimum And 1.968 Inches Maximum                                     |
| <b>Head Style:</b>                               | Dished Hexagon  |
| <b>Head Height:</b>                              | 0.188 Inches Minimum And 0.203 Inches Maximum                                     |
| <b>Width Between Flats:</b>                      | 0.554 Inches Minimum And 0.564 Inches Maximum                                     |
| <b>Grip Diameter:</b>                            | 0.374 Inches Minimum And 0.375 Inches Maximum                                     |
| <b>Nominal Thread Diameter:</b>                  | 0.375 Inches  |
| <b>Grip Length:</b>                              | 1.365 Inches Minimum And 1.385 Inches Maximum                                     |
| <b>Thread Quantity Per Inch:</b>                 | 24  |
| <b>Minimum Tensile Strength:</b>                 | 160000 Pounds Per Square Inch   |
| <b>Part Name Assigned By Controlling Agency:</b> | Bolt Hex Head Close Tolerance A286 Cres Long Threads Self Locking And Non Locking |
| <b>Material:</b>                                 | Iron Alloy 660 Overall  |
| <b>Surface Treatment:</b>                        | Cadmium Overall And Chromate Overall  |
| <b>Thread Series Designator:</b>                 | Unjf  |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6706D22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.