

P/N NAS6706D62

Description

Fastener Length: 4-7/16", Thread: 3/8-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6706D62

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-542-3122

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6706D62 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	4.453 Inches Nominal
Head Style:	Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.374 Inches Nominal
End Item Identification:	Aircraft, Osprey V-22a
Nominal Thread Diameter:	0.375 Inches
Grip Length:	3.875 Inches Nominal
Thread Quantity Per Inch:	24
Special Features:	Head And Shank Drilled For Safety Wire And Cotter Pin.
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6706D62 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.