

Description

Fastener Length: 4-7/16", Thread: 3/8-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6706D62
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-542-3122
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6706D62 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	4.453 Inches Nominal
Head Style:	Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.374 Inches Nominal
End Item Identification:	Aircraft, Osprey V-22a
Nominal Thread Diameter:	0.375 Inches
Grip Length:	3.875 Inches Nominal
Thread Quantity Per Inch:	24
Special Features:	Head And Shank Drilled For Safety Wire And Cotter Pin.
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6706D62> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.