

**Description**

Fastener Length: 1-13/64", Hole Diameter: 5/64", Thread: 3/8-24, Thread Length: 9/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6706H10                                |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-01-577-9298                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6706H10 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                             | 3a   |
| <b>Thread Direction:</b>                         | Right-hand   |
| <b>Thread Length:</b>                            | 0.578 Inches Nominal   |
| <b>Fastener Length:</b>                          | 1.188 Inches Minimum And 1.218 Inches Maximum  |
| <b>Head Style:</b>                               | Dished Hexagon   |
| <b>Head Height:</b>                              | 0.188 Inches Minimum And 0.203 Inches Maximum  |
| <b>Width Between Flats:</b>                      | 0.554 Inches Minimum And 0.564 Inches Maximum  |
| <b>Hole Diameter:</b>                            | 0.070 Inches Minimum And 0.080 Inches Maximum  |
| <b>Grip Diameter:</b>                            | 0.374 Inches Minimum And 0.375 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>                  | 0.375 Inches   |
| <b>Grip Length:</b>                              | 0.615 Inches Minimum And 0.635 Inches Maximum  |
| <b>Hole Quantity:</b>                            | 3  |
| <b>Hole Type:</b>                                | Drilled  |
| <b>Thread Quantity Per Inch:</b>                 | 24   |
| <b>Minimum Tensile Strength:</b>                 | 160000 Pounds Per Square Inch  |
| <b>Part Name Assigned By Controlling Agency:</b> | Bolt Tension Hex Head Close Tolerance A286 Cres Long Thread Reduced Major Thread Dia. Self Locking And Non Locking 160 Ksi Ftu |
| <b>Material:</b>                                 | Iron Alloy 660 Overall   |
| <b>Surface Treatment:</b>                        | Cadmium Overall And Chromate Overall   |
| <b>Thread Series Designator:</b>                 | Unjf   |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6706H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.