

Description

Thread: 3/8-24, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6706U13
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-542-8014
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6706U13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6706U13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.