

# P/N NAS6706U18

### **Description**

Fastener Length: 1-45/64", Thread: 3/8-24, Thread Length: 9/16", NAS6706 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS6706U18

Minimum Qty (MOQ):

NSN: 5306-01-447-6361

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS6706U18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.5778 Inches Nominal
Fastener Length:	1.688 Inches Minimum And 1.718 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6706 Professional/industrial Association Standard

## **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6706U18">https://military-fasteners.com/bolts/shear+bolts/NAS6706U18</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.