

Description

Fastener Length: 61/64", Thread: 3/8-24, Thread Length: 9/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS6706U6
Minimum Qty (MOQ):	2
NSN:	5306-01-591-7924
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS6706U6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	0.938 Inches Minimum And 0.968 Inches Maximum
Head Style:	Hexagon
Head Height:	0.973 Inches Minimum And 1.003 Inches Maximum
Width Between Flats:	0.554 Nominal Mils And 0.564 Nominal Centimeters
Grip Diameter:	0.374 Nominal Mils And 0.375 Nominal Centimeters
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.365 Nominal Mils And 0.385 Nominal Centimeters
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt,tension,hex Head,close Tolerance,a286 Cres
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731,ams5732,ams5737 Or Ams5853 Cres-a286 (uns S66286) Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6706U6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.