

Description

Fastener Length: 2-3/16", Thread: 3/8-20, Thread Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6707D24
Minimum Qty (MOQ):	2
NSN:	5306-01-573-8142
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6707D24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	2.194 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.436 Inches Minimum And 0.437 Inches Maximum
End Item Identification:	Nimrod 2000;nimrod Mra4
Nominal Thread Diameter:	0.437 Inches
Grip Length:	1.490 Inches Minimum And 1.510 Inches Maximum
Thread Quantity Per Inch:	20
Part Name Assigned By Controlling Agency:	Close Tolerance Hex Head Bolt
Special Features:	Close Tolerance Bolt,drilled Shank,undrilled Hexhead,non-locking
Color:	Green Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall Or Ams5853 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type li.class 2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6707D24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.