

Description

Fastener Length: 2-3/16", Thread: 3/8-20, Thread Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6707D24 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5306-01-573-8142 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS6707D24 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.694 Inches Nominal |
| Fastener Length: | 2.194 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.219 Inches Minimum And 0.234 Inches Maximum |
| Width Between Flats: | 0.678 Inches Minimum And 0.690 Inches Maximum |
| Grip Diameter: | 0.436 Inches Minimum And 0.437 Inches Maximum |
| End Item Identification: | Nimrod 2000;nimrod Mra4 |
| Nominal Thread Diameter: | 0.437 Inches |
| Grip Length: | 1.490 Inches Minimum And 1.510 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Part Name Assigned By Controlling Agency: | Close Tolerance Hex Head Bolt |
| Special Features: | Close Tolerance Bolt,drilled Shank,undrilled Hexhead,non-locking |
| Color: | Green Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std 1st Material Response Overall Or Ams5853 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type li.class 2 Fed Spec 1st Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6707D24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.