

**Description**

Fastener Length: 2-3/16", Thread: 3/8-20, Thread Length: 11/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6707D24
Minimum Qty (MOQ):	2
NSN:	5306-01-573-8142
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6707D24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.694 Inches Nominal
<b>Fastener Length:</b>	2.194 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.219 Inches Minimum And 0.234 Inches Maximum
<b>Width Between Flats:</b>	0.678 Inches Minimum And 0.690 Inches Maximum
<b>Grip Diameter:</b>	0.436 Inches Minimum And 0.437 Inches Maximum
<b>End Item Identification:</b>	Nimrod 2000;nimrod Mra4
<b>Nominal Thread Diameter:</b>	0.437 Inches
<b>Grip Length:</b>	1.490 Inches Minimum And 1.510 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Part Name Assigned By Controlling Agency:</b>	Close Tolerance Hex Head Bolt
<b>Special Features:</b>	Close Tolerance Bolt,drilled Shank,undrilled Hexhead,non-locking
<b>Color:</b>	Green Threads
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std 1st Material Response Overall Or Ams5853 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type li.class 2 Fed Spec 1st Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6707D24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.