

Description

Fastener Length: 2-1/4", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS6707D25
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-518-1489
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6707D25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	2.256 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.686 Inches Nominal
Grip Diameter:	0.764 Inches Nominal
Shank Unthreaded Hole Diameter:	0.440 Inches Nominal Overall
Nominal Thread Diameter:	0.4375 Inches
Grip Length:	1.562 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	1600000 Pounds Per Square Inch
Special Features:	W/drilled Shank
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6707D25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.