

**Description**

Fastener Length: 2-1/4", Thread: 7/16-20, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6707D25
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-518-1489
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6707D25 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.694 Inches Nominal
<b>Fastener Length:</b>	2.256 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.219 Inches Nominal
<b>Width Between Flats:</b>	0.686 Inches Nominal
<b>Grip Diameter:</b>	0.764 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.440 Inches Nominal Overall
<b>Nominal Thread Diameter:</b>	0.4375 Inches
<b>Grip Length:</b>	1.562 Inches Nominal
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	1600000 Pounds Per Square Inch
<b>Special Features:</b>	W/drilled Shank
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6707D25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.