

Description

Fastener Length: 1-45/64", Thread: 3/8-20, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6707DU16 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-330-0433 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS6707DU16 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.090 Inches Minimum And 1.010 Inches Maximum |
| Fastener Length: | 1.679 Inches Minimum And 1.709 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.219 Inches Minimum And 0.234 Inches Maximum |
| Width Between Flats: | 0.678 Inches Minimum And 0.690 Inches Maximum |
| Grip Diameter: | 0.4365 Inches Minimum And 0.4370 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.437 Inches |
| Grip Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.985 Inches Minimum First Hole And 1.015 Inches Maximum First Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6707 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6707DU16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.