

Description

Fastener Length: 1-53/64", Thread: 3/8-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6707DU18
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-579-6671
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6707DU18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	1.804 Inches Minimum And 1.834 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.436 Inches Minimum And 0.437 Inches Maximum
Nominal Thread Diameter:	0.437 Inches
Grip Length:	1.819 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt Tension Hex Head Close Tolerance A286 Cres Long Thread Reduced Major Thread Dia Self Locking And Non Locking 160 Ksi Ftu
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6707DU18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.