



Military-Fasteners.com

P/N NAS6707DU18

Description

Fastener Length: 1-53/64", Thread: 3/8-20, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6707DU18
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-579-6671
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6707DU18 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.694 Inches Nominal
<b>Fastener Length:</b>	1.804 Inches Minimum And 1.834 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.219 Inches Minimum And 0.234 Inches Maximum
<b>Width Between Flats:</b>	0.678 Inches Minimum And 0.690 Inches Maximum
<b>Grip Diameter:</b>	0.436 Inches Minimum And 0.437 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.437 Inches
<b>Grip Length:</b>	1.819 Inches Nominal
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Bolt Tension Hex Head Close Tolerance A286 Cres Long Thread Reduced Major Thread Dia Self Locking And Non Locking 160 Ksi Ftu
<b>Material:</b>	Iron Alloy 660 Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6707DU18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.