

Description

Fastener Length: 2-1/8", Thread: 1/2-20, Thread Length: 47/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6708DU22
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-531-0802
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS6708DU22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Nominal
Fastener Length:	2.095 Inches Minimum And 2.125 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.448 Inches Minimum And 0.449 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708DU22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.