

**Description**

Fastener Length: 2-5/16", Thread: 1/2-20, Thread Length: 47/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6708DU25                               |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5306-01-456-3724                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6708DU25 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.735 Inches Nominal  |
| <b>Fastener Length:</b>   | 2.282 Inches Minimum And 2.312 Inches Maximum                       |
| <b>Head Style:</b>  | Dished Hexagon  |
| <b>Head Height:</b>   | 0.250 Inches Minimum And 0.265 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.741 Inches Minimum And 0.752 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.4990 Inches Minimum And 0.4995 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.500 Inches  |
| <b>Grip Length:</b>   | 1.552 Inches Minimum And 1.570 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>  | 20  |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch                                       |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.994 Inches Minimum First Hole And 2.044 Inches Maximum First Hole |
| <b>Material:</b>  | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>                            | Ams5731 Assn Std Single Material Response Overall                   |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-35 Fed Spec Single Treatment Response Overall                  |
| <b>Thread Series Designator:</b>  | Unjf  |
| <b>Specification/standard Data:</b>                                     | 80205-nas6705 Professional/Industrial Association Standard          |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708DU25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.