

Description

Fastener Length: 9/64", Thread: 1/2-20, Thread Length: 47/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6708DU58
Minimum Qty (MOQ):	1
NSN:	5306-01-491-9315
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6708DU58 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.7350 Inches Nominal
Fastener Length:	0.1466 Inches Minimum And 0.1497 Inches Maximum
Head Style:	Hexagon
Head Height:	0.2500 Inches Minimum And 0.2650 Inches Maximum
Width Between Flats:	0.7410 Inches Minimum And 0.7520 Inches Maximum
Grip Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.5000 Inches
Grip Length:	0.7350 Inches Minimum And 0.7620 Inches Maximum
Thread Quantity Per Inch:	20
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708DU58> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.