

Description

Fastener Length: 1-3/8", Thread: 1/2-20, Thread Length: 47/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6708U10
Minimum Qty (MOQ):	1
NSN:	5306-01-499-3574
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6708U10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Nominal
Fastener Length:	1.345 Inches Minimum And 1.375 Inches Maximum
Head Style:	Hexagon
Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
End Item Identification:	F-22
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Blot, Hex Head, Close Tolerance, A286 Cres, Long Threads, Non-locking
Special Features:	Requested Namebolt, Hex Head
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5853 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708U10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.