

**Description**

Fastener Length: 1-3/8", Thread: 1/2-20, Thread Length: 47/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS6708U10
Minimum Qty (MOQ):	1
NSN:	5306-01-499-3574
ECCN:	EAR99



## P/N NAS6708U10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.735 Inches Nominal
<b>Fastener Length:</b>	1.345 Inches Minimum And 1.375 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.250 Inches Minimum And 0.265 Inches Maximum
<b>Width Between Flats:</b>	0.741 Inches Minimum And 0.752 Inches Maximum
<b>Grip Diameter:</b>	0.4990 Inches Minimum And 0.4995 Inches Maximum
<b>End Item Identification:</b>	F-22
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Blot, Hex Head, Close Tolerance, A286 Cres, Long Threads, Non-locking
<b>Special Features:</b>	Requested Namebolt, Hex Head
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5853 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708U10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.