

Description

Fastener Length: 1-7/16", Thread: 1/2-20, Thread Length: 47/64", NAS6708 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6708U11
Minimum Qty (MOQ):	1
NSN:	5306-01-613-1475
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6708U11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Nominal
Fastener Length:	1.408 Inches Minimum And 1.438 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.499 Inches Minimum And 0.500 Inches Maximum
End Item Identification:	Strainer, Sed
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt Tension Hex Head Close Tolerance
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708U11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.