

Description

Fastener Length: 1-11/16", Thread: 1/2-20, Thread Length: 47/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6708U15 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-360-4831 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



P/N NAS6708U15 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.735 Inches Nominal |
| Fastener Length: | 1.658 Inches Minimum And 1.688 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.250 Inches Minimum And 0.265 Inches Maximum |
| Width Between Flats: | 0.741 Inches Minimum And 0.752 Inches Maximum |
| Grip Diameter: | 0.4990 Inches Minimum And 0.4995 Inches Maximum |
| Nominal Thread Diameter: | 0.500 Inches |
| Grip Length: | 0.928 Inches Minimum And 0.948 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6708 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708U15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.