

Description

Fastener Length: 1-3/4", Thread: 1/2-20, Thread Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6708U16
Minimum Qty (MOQ):	1
NSN:	5306-01-284-1374
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6708U16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.710 Inches Minimum And 0.760 Inches Maximum
Fastener Length:	1.720 Inches Minimum And 1.750 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6708 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708U16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.