

**Description**

Fastener Length: 2-3/8", Thread: 1/2-20, Thread Length: 47/64", NAS6708 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6708U26
Minimum Qty (MOQ):	1
NSN:	5306-01-442-8352
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS6708U26 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.735 Inches Nominal
<b>Fastener Length:</b>	2.345 Inches Minimum And 2.375 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.250 Inches Minimum And 0.266 Inches Maximum
<b>Width Between Flats:</b>	0.741 Inches Minimum And 0.752 Inches Maximum
<b>Grip Diameter:</b>	0.4990 Inches Minimum And 0.4995 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	1.615 Inches Minimum And 1.635 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5853 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6708 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708U26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.