

Description

Fastener Length: 2-7/8", Thread: 1/2-20, Thread Length: 47/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6708U34
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-498-6768
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS6708U34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Nominal
Fastener Length:	2.845 Inches Minimum And 2.875 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.499 Inches Nominal
Single Shear Strength:	95000 Pounds Per Square Inch
End Item Identification:	F/a-22 Raptor
Nominal Thread Diameter:	0.500 Inches
Grip Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt, Hex Head
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 National Std/spec 1st Material Response Overall Or Ams 5737 National Std/spec 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 National Std/spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205 - Nas 6708 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6708U34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.