

Description

Fastener Length: 2-7/8", Thread: 9/16-18, Thread Length: 13/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6709DU33
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-498-6742
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6709DU33 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.840 Inches Nominal
<b>Fastener Length:</b>	2.903 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.281 Inches Nominal
<b>Width Between Flats:</b>	0.865 Inches Minimum And 0.877 Inches Maximum
<b>Grip Diameter:</b>	0.561 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.141 Inches Nominal First Hole
<b>End Item Identification:</b>	F-22 Raptor
<b>Nominal Thread Diameter:</b>	0.563 Inches
<b>Grip Length:</b>	2.063 Inches Nominal
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.712 Inches Nominal First Hole
<b>Part Name Assigned By Controlling Agency:</b>	Bolt,hex Head,close Tolerance,a286 Cres,long Threads,nonlocking
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6709DU33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.