

Description

Fastener Length: 2-7/8", Thread: 9/16-18, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6709DU33
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-498-6742
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6709DU33 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.840 Inches Nominal
Fastener Length:	2.903 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Grip Diameter:	0.561 Inches Nominal
Shank Unthreaded Hole Diameter:	0.141 Inches Nominal First Hole
End Item Identification:	F-22 Raptor
Nominal Thread Diameter:	0.563 Inches
Grip Length:	2.063 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.712 Inches Nominal First Hole
Part Name Assigned By Controlling Agency:	Bolt,hex Head,close Tolerance,a286 Cres,long Threads,nonlocking
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6709DU33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.