

Description

Fastener Length: 1-21/32", Thread: 1/2-18, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6709U13 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-360-4827 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |



P/N NAS6709U13 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.840 Inches Nominal |
| Fastener Length: | 1.637 Inches Minimum And 1.667 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.281 Inches Minimum And 0.296 Inches Maximum |
| Width Between Flats: | 0.865 Inches Minimum And 0.877 Inches Maximum |
| Grip Diameter: | 0.5610 Inches Minimum And 0.5615 Inches Maximum |
| Nominal Thread Diameter: | 0.562 Inches |
| Grip Length: | 0.802 Inches Minimum And 0.822 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6709 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6709U13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.