

Description

Fastener Length: 1-23/32", Thread: 1/2-18, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6709U14
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-360-4828
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS6709U14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.840 Inches Nominal
Fastener Length:	1.700 Inches Minimum And 1.730 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.281 Inches Minimum And 0.296 Inches Maximum
Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Grip Diameter:	0.5610 Inches Minimum And 0.5615 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6709 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6709U14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.