

**Description**

Fastener Length: 1-27/32", Thread: 1/2-18, Thread Length: 13/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS6709U16       |
| Minimum Qty (MOQ): | 1 EA             |
| NSN:               | 5306-01-360-4830 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N NAS6709U16 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.840 Inches Nominal   |
| <b>Fastener Length:</b>                               | 1.825 Inches Minimum And 1.855 Inches Maximum  |
| <b>Head Style:</b>                                    | Dished Hexagon   |
| <b>Head Height:</b>                                   | 0.281 Inches Minimum And 0.296 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.865 Inches Minimum And 0.877 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.5610 Inches Minimum And 0.5615 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>                       | 0.562 Inches   |
| <b>Grip Length:</b>                                   | 0.990 Inches Minimum And 1.010 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 18   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas6709 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6709U16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.