

# P/N NAS6709U17

### **Description**

Fastener Length: 1-29/32", Thread: 1/2-18, Thread Length: 13/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS6709U17
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-435-4801
Schedule B:	7318.15.8085
FCCN:	9A991



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS6709U17 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.840 Inches Nominal
Fastener Length:	1.887 Inches Minimum And 1.917 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.281 Inches Minimum And 0.296 Inches Maximum
Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Grip Diameter:	0.5610 Inches Minimum And 0.5615 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	1.052 Inches Minimum And 1.072 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Minimum Yield Strength:	95000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Fastener
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6709 Professional/industrial Association Standard

### **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6709U17">https://military-fasteners.com/bolts/shear+bolts/NAS6709U17</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.