

Description

Fastener Length: 2-23/32", Thread: 5/8-18, Thread Length: 59/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6710DU29
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-558-9784
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6710DU29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.877 Inches Minimum And 0.927 Inches Maximum
Fastener Length:	2.699 Inches Minimum And 2.729 Inches Maximum
Head Style:	Dished Hexagon
Width Between Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Grip Diameter:	0.6235 Inches Minimum And 0.6240 Inches Maximum
Shank Unthreaded Hole Diameter:	0.136 Inches Minimum First Hole And 0.146 Inches Maximum First Hole
Nominal Thread Diameter:	0.625 Inches
Grip Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.465 Inches Minimum First Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6710DU29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.