

Description

Fastener Length: 2-23/32", Thread: 5/8-18, Thread Length: 59/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6710DU29
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-558-9784
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6710DU29 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.877 Inches Minimum And 0.927 Inches Maximum
<b>Fastener Length:</b>	2.699 Inches Minimum And 2.729 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Width Between Flats:</b>	0.928 Inches Minimum And 0.940 Inches Maximum
<b>Grip Diameter:</b>	0.6235 Inches Minimum And 0.6240 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.136 Inches Minimum First Hole And 0.146 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.625 Inches
<b>Grip Length:</b>	2.115 Inches Minimum And 2.135 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.465 Inches Minimum First Hole
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6710DU29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.