

Description

Fastener Length: 2-1/32", Thread: 5/8-18, Thread Length: 29/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6710DU30
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-578-5423
Schedule B:	7318.15.8085
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N NAS6710DU30 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.892 Inches Minimum And 0.912 Inches Maximum
<b>Fastener Length:</b>	2.012 Inches Minimum And 2.042 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.312 Inches Minimum And 0.327 Inches Maximum
<b>Width Between Flats:</b>	0.920 Inches Minimum And 0.940 Inches Maximum
<b>Grip Diameter:</b>	0.623 Inches Minimum And 0.624 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.625 Inches
<b>Grip Length:</b>	1.875 Inches Nominal
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6710DU30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.