

Description

Fastener Length: 2-1/32", Thread: 5/8-18, Thread Length: 29/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6710DU30 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-578-5423 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS6710DU30 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.892 Inches Minimum And 0.912 Inches Maximum |
| Fastener Length: | 2.012 Inches Minimum And 2.042 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.312 Inches Minimum And 0.327 Inches Maximum |
| Width Between Flats: | 0.920 Inches Minimum And 0.940 Inches Maximum |
| Grip Diameter: | 0.623 Inches Minimum And 0.624 Inches Maximum |
| Nominal Thread Diameter: | 0.625 Inches |
| Grip Length: | 1.875 Inches Nominal |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6710DU30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.